Plant	Client	Contract Code	Document ID		Co	ntract N	No.		
300 MTPD Caustic Soda Expansion	PACL	PACL- 300 TPD EXPN 0215-EQS-11-EC-0001							
thyssenkrupp	Cell Rack Ind	chnical specificluding Pressure Dev (Ton No. 11A01AN	vice & Bus Bar System I-FNZ01)			DQC EL LIM)	
	UPGN	ADATION OF CAUST	IC SODA FLANI	Rev	00	Page	1	of	5

TKIS - Ind	ia / <u>Vendor</u>	TKIS - Ir	ndia /	Owner / Client							
	1 For Approval	· I	1	For Approval							
ੂ⊟	2 For Review / Comments	Ī	2	For Review / Comments							
□	3 For Information	i	3	For Information							
es a	4 For Engineering	es es	4	For Engineering							
Sodi Sodi	5 For Enquiry	Do Codi	5	For Enquiry							
Category Codes (Submission Purpose)	6 For Order Placement	Category Codes (Submission Purpose)	6	For Order Placement							
rego missi	7 Final & Approved	missi	7	Final & Approved							
Cat (Sub	8 Released for Construction	Cat (Sub	8	Released for Construction							
		Acceptance Codes (Approval Codes)	1 2 3 4 5 6	Approved Approved for Manufacturing / Fabrication with Comments as marked Not Approved / Resubmit Retained for Information / Records Reviewed Reviewed as Noted / Resubmit							
Remarks for AC2: This marked-up drawings is hereby approved for fabrication / manufacturing and shall be re-sbumitted after revision. This drawing should be revised only to the extent of TKIS - India / Owner / Client comments. Any other changes made by you will not be considered unless clearly highlighted in covering letter asking for approval. This approval / review does not absolve the supplier from the full responsibility for design and fabrication.											
Date ://	Name :	Date ://		Name :							

00	_	Issued for Enquiry	01.11.18	ADV	02.11.18	GBP	02.11.18	GBP	<u> </u>
Rev.	Status	Description	Date	Prepared	Date	Checked	Date	Approved	AC
© Cop thysse	oyright 2018 nkrupp Indus	s : All rights reserved strial Solutions (India) Private Limited			Bar	code			Category Code: - 05

Plant	Client	Contract Code	Document ID	Contract No.		
300 MTPD Caustic Soda Expansion	PACL	PACL- 300 TPD EXPN	0215-EQS-11-EC-0001	66-0215		
thyssenkrupp	Cell Rack Ind	cluding Pressure Dev	hnical specification for uding Pressure Device & Bus Bar System (Ton No. 11A01AN-FNZ01)			

00 Page 2 of 5

Rev

LIST	LIST OF DRAWINGS									
SR. NO	1.1 DESCRIPTION									
1.	(0200) General Assembly Cell Rack and Current Supply – 0215-EQS-11-TB-0001 Sht.1/2	00								
2.	(0200) Details Cell Rack and Current Supply – 0215-EQS-11-TB-0001 Sht.2/2	00								
3.	(0201) Cell Rack - 0215-EQS-11-TB-0002 Sht.1/3	00								
4.	(0201) Cell Rack Bolt holes on bottom flange on H beam - 0215-EQS-11-TB-0002 Sht.2/3	00								
5.	(0201.60) Intermediate Plate - 0215-EQS-11-TB-0002 Sht.3/3	00								
6	(0202) Pressure Plate - 0212-EQS-11-TB-0003 Sht. 1/1	00								
7.	(0201.51, 0210, 0216, 0267, 0268, 0287A) Parts of Insulation – 0215-EQS-11-TB-0004 Sht. 1/1	00								
8.	(0205, 0207,0230) Rack Insulators, Insulators - 0215-EQS-11-TB-0005 Sht. 1/1	00								
9.	(0211, 0212A/B, 0213, 0215, 0217) Parts for Pressure Devices - 0215-EQS-11-TB-0006 Sht.1/1	00								
10.	(0206, 0208, 0233, 0260, 0260A, 0261) Detail of Supports for Headers and other parts - 0215-EQS-11-TB-0007 Sht. 1/1	00								
11.	(0400) Personal Protection General Arrangement and Details - 0215-EQS-11-TB-0008 Sht.1/1	00								
12.	(0221A/B, 0222A/B) Detail of Busbars - 0215-EQS-11-TB-0009 Sht. 1/1	00								
13.	(0223A/B, 0229, 0270) Detail of Copper Flexibles - 0215-EQS-11-TB-0010 Sht. 1/1	00								
14.	(0288, 0289) Detail of Instrument cable Duct - 0215-EQS-11-TB-0011 Sht. 1/1	00								
15.	(0226, 0227) Detail of Busbars - 0215-EQS-11-TB-0012 Sht. 1/1	00								
16.	(0280) Tightening sequence for pressure bolts - 0215-EQS-11-TB-0013 Sht. 1/1	00								
17.	(0214) Conical Spring 34/16.3/1.5 Gr.2 – 0215-EQS-11-TB-0014 Sht. 1/1	00								
18.	(0250) Guide Rail – 0215-EQS-11-TB-0015 Sht. 1/1	00								
19.	(0201.74, 0293) Details for insulation cap – 0215-EQS-11-TB-0016 Sht.1/1	00								
20.	(12H003) Element lifting beam - 0215-EQS-12-TB-0035 Sht 1/1	00								
21.	(0218, 0219) Details for earthquake safety device 0215-EQS-11-TB-0017 Sht.1/1	00								
22.	(0221A/B, 0222A/B) Technical specs of Copper Busbars - 0215-ELT-11-EC-0004	00								
23.	(0223A/B, 0270, 0229)Technical specs for Copper Flexibles – 0215-ELT-11-EC-0002	00								
24.	(0226, 0227) Technical specs of Copper Busbars - 0215-ELT-11-EC-0004	00								

Plant	Client	Client Contract Code Document ID						Contract No.							
300 MTPD Caustic Soda Expansion	1 PACI 1 10215-E08-11-EC-0001				66-0215										
thyssenkrupp	Cell Rack Inc	chnical specificuling Pressure Devotors (Ton No. 11A01AN	rice & Bus Bar System -FNZ01)			LIMI		ſ							
	0.0		Rev	00	Page	3	of	5							

1. SCOPE OF SUPPLY

3.

- Supply, fabrication, painting, assembly, transportation and supervision of erection of cell rack assembly of electrolyser at PACL, Panjab Nayanangal site as per the drawings enclosed herewith (for list of drawings enclosed refer Page 2).
- (b) Part Nos. 0223A/B, 0226, 0227, 0229 and 0270 (as applicable) shall be supplied by copper busbar manufacturer.

Vendor shall supervise erection at above listed bus bars along with cell rack assembly at site. Vendor shall quote man day basis Separately for supervision activity at site.

- (c) Part no. 0221A/B and 0222A/B shall be supplied by cellrack vendor.
- 2. (a) No. of cell rack assembly per electrolyser 2 Nos.
 - (b) No. of electrolysers 6 Nos.Hence Total No. of Cell Rack assemblies 12 Nos.

Surface preparation: Blast cleaning to Swedish Std. Sa. 2-1/2.

Painting: One coat of inorganic zinc silicate primer of 75 microns DFT. Inert Pigment / Epoxy resin 60 microns DFT as first top coat and 65 microns as second top coat. Total DFT 200 microns.

- 4. All bolts, nuts, washers, slotted counter sunk head screw, fasteners (except disc spring item No.0214) shall be zinc coated as per DIN 267 to A2E coating scheme. Item Nos. 0201.01, 0201.02, 0201.04, 0201.05 & 0201.07 have to be zinc hot dip galvanized according to DIN EN ISO 10684.
- 5. Conical springs, part No.0214 shall be according to drawing no. 0215-EQS-11-TB-0014.
- 6. Fabrication, Welding & Erection: As per good engineering practice and to the satisfaction of inspection of CLIENT / tklS India.

Plant 300 MTPD Caustic Soda Expansion	PACL PACL	Contr							
thyssenkrupp	Cell Rack Inc	chnical specifichnical specifichler Eluding Pressure Dev (Ton No. 11A01AN ADATION OF CAUST	vice & Bus Bar System -FNZ01)	Rev	PAC) QC L LIMI)	5

- 7. All notes indicated in Drg. No. 0215-EQS-11-TB-0001 are applicable.
- 8. If required, vendor can prepare detailed fabrication drawings for their shop. (These drawings need not be submitted to tkIS India).
- Vendor to submit samples and chemical and mechanical properties of following items to tklS (India) / Client for approval before procuring the same.
 Part Nos. 0201.51, 0205, 0207,0230, 0210, 0214, 0216, 0267, 0268, 0287A, 0293, 0401A, 0401B, 0401C, 0401D, 0401E, 0401F & 0402A/B.
- 10. All cell racks have to be assembled at the manufacturer's shop for final inspection and dispatch to site in assembled condition.
- 11. Ref. Drg. No. 0215-EQS-11-TB-0004: All the insulation parts (i.e. Part No.-0201.51, 0210, 0216, 0267, 0268, 0287A) shall be fabricated in one piece (i.e. without any joints).
- 12. Inspection by CLIENT / tklS (India).
- 13. All materials shall be supplied with test certificate.
- 14. All bolts, nuts, washers, counter sunk screws, springs shall be supplied with minimum 2% spare. Total quantity of spares for all electrolysers are noted in Drg. No. 0215-EQS-11-TB-0001.
- 15. Vendor shall check the foundation offered for erection prior to start up any activity.

300 MTPD Caustic Soda Expansion PACL PACL-300 TPD EXPN 0215-EQS-11-EC-0001 66-0215 Technical specification for Cell Rack Including Pressure Device & Bus Bar System	Plant	Client	Contract No.							
		PACL		10215-E0S-11-EC-0001 1				5		
thyssenkrupp (Ton No. 11A01AN-FNZ01) UPGRADATION OF CAUSTIC SODA PLANT Rev 00 Page 5 of	thyssenkrupp	Cell Rack Inc	luding Pressure Dev (Ton No. 11A01AN	vice & Bus Bar System -FNZ01)		PAC	L LIM	ITED		5

EQUIVALENT MATERIAL SPECIFICATION FOR INSULATION PLATE UP GM 201 WHITE DIN EN 60893 (=HM2471 DIN 7735) / HM 2472

Glass fibre mat reinforced Unsaturated polyster resin bonded laminated sheet with good water resistance and machining characteristics. The insulating material shall conform to minimum requirements given below: Values () are typical values intended to give only general guidance and are not to be considered as requirements of this standard.

		Test			Nominal	Type	
		method in		Max.	thickness of		
	Property	IEC 893-2	Unit	or	sheet to which	UP GM	Remarks
				Min.	test is applicable	201	
		Subclause			mm		
	Flexural stress at						
1	rupture	5.1	MPa	Min.	≥ 1.6	130	
_	perpendicular to	3.1	IVII U		₹ 1.0	130	
	laminations						
2	Apparent module of	5.2	MPa	Min.	≥ 1.6	(8 000)	
	elasticity in flexure	3.2	IVII U	141111.	≥ 1.0	(6 600)	
	Compressive						
3	strength	5.3	MPa	Min.	≥5	(200)	
	perpendicular to					(/	
	laminations						
	Impact strength		2				The requirement for impact strength
4	(Charpy) parallel to	5.5.2	kJ/m²	Min.	≥5	40	Charpy and Izod are alternative. A
	laminations						material meeting either requirements
_	Impact strength	5.5.2	1.1/2	N 41:	\ r	25	shall be deemed to comply with the
5	(Izod) parallel to	5.5.3	kJ/m²	Min.	≥5	35	specification
	laminations Shearing strength						
6	parallel to	5.6	MPa	Min.	≥5	(20)	
0	laminations	5.0	IVIPa	IVIIII.	23	(20)	
7	Tensile strength	5.7	MPa	Min.	≥ 1.6	(70)	
	Electric strength at	5.7	IVII a	IVIIII.	2 1.0	(70)	
	90°C in oil					AS PER EN 60893-3-5	
8	perpendicular to	6.1.2	kV/mm	Min.	≤ 3	(Table 5)	
	laminations					(122.2.2)	
	Breakdown voltage						
9	at 90°C in oil parallel	6.1.3	kV	Min.	>3	35	
	to laminations				-		
40-	Permittivity at 48	6.3			4.3	4.5	0 ()
10a	Hz-62 Hz	6.2		Max.	≤3	4.5	Conformance with the requirement for
4.01-	Permittivity at 1	6.3			4.3	4.5	either test constitutes conformance with
10b	MHz	6.2		Max.	≤3	4.5	the specification in this respect
11a	Dissipation factor at	6.2		Max.	≤3	0.05	Conformance with the requirement for
114	48 Hz-62 Hz	0.2		IVIAX.	2.5	0.05	either test constitutes conformance with
11b	Dissipation factor at	6.2	_	Max.	≤3	0.05	the specification in this respect
110	1 MHz	0.2		IVIUX.	= 3	0.05	the specification in this respect
	Insulation resistant					2	
12	after immersion in	6.3	$M\Omega$	Min.	All	5 x 10 ²	
	water						
13	Proof tracking index	6.4	-	-	≥3	500	
14	Comparative	6.4	-	Min.	≥3	(600)	
	tracking index					(/	
15	Tracking and erosion	6.5	Class	Min.	-		Method 1 of IEC 587
	resistance					(4.20)	
16	Thermal endurance	7.1	T.I.		≥3	(130)	
17	Flammability	7.2	Category		3		
10	Temperature of	7.2	°C			. Hadan sansidan (1	
18	deflection under	7.3	C			Under consideration	
10	load	0.1	a/s3	Dones	Δ.!.		
19	Density	8.1	g/cm ³	Range	All	AS PER EN 60893-3-5	
20	Water absorption	8.2	mg	Max.	All	(Table 7)	
		<u> </u>		l	l .	(Tuble //	